

REMOTE CONTROL JACKS – PLAIN RAM



Remote Control Type Hydraulic Jacks Plain Ram



DESCRIPTIONS								
Model No.	Capacity in Tons	Closed Height mm.	Power Lift mm.	Total Ext. Hight mm.	Ram Dia mm.	Body Dia mm.	Pump Piston No.	Approx Weight
5	5	250	150	400	45	64	one	6
10	10	255	150	405	50	80	one	12
15	15	265	150	415	65	100	one	15
20	20	280	150	425	70	110	one	18
25	25	280	150	430	75	115	one	22
30	30	285	150	435	85	127	one	26
50	50	305	150	455	95	150	Two	45
100	100	320	150	470	145	210	Two	75
150	150	335	150	475	185	275	Two	160
200	200	335	150	485	200	325	Two	185
300	300	350	150	500	270	400	Two	240
400	400	400	150	550	310	445	Two	420
500	500	400	150	550	340	480	Two	580
1000	1000	440	150	590	460	620	Two	760

* * The above jacks are worked by detached hand-operated high pressure pump connected to the jack by steel or flexible tubing or high pressuer rubber house.

* * Pressure Gauge can be fitted when required.

* * Manufacturing Tolerance ± 10 mm .

* * The specification and description are only indicative and subject to change without any notice .